



Deutsche
Qualität
Garantiert

METEOR
N-TYPE TOPCON TECHNOLOGY

CMER-108BDE 480W-500W

More power, less degradation

22.47%

MAXIMUM EFFICIENCY

108

HALF CELLS

30 YEARS
Performance Warranty

up to **30 YEARS***
Product Warranty

*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. for extensions, please contact AESOLAR staff.



LID
RESISTANT



PID
RESISTANT



SALT CORROSION
RESISTANT




SAND
RESISTANT



AMMONIA
RESISTANT




HIGHLY STABLE
AND TOUGH




BIFACIAL
DOUBLE-GLASS

OUR PERFORMANCE WARRANTY



SYSTEM AND PRODUCT CERTIFICATIONS




www.ae-solar.com

AE CMER-108BDE 480W-500W

N-TYPE TOPCON TECHNOLOGY PV MODULE

BIFACIAL • DOUBLE-GLASS



Electrical specifications (STC*):

Nominal max. power	P_{max} (Wp)	480	485	490	495	500
Maximum operating voltage	V_{MPP} (V)	32.80	33.00	33.20	33.40	33.60
Maximum operating current	I_{MPP} (A)	14.63	14.70	14.76	14.82	14.88
Open-circuit voltage	V_{oc} (V)	38.90	39.10	39.30	39.50	39.70
Short-circuit current	I_{sc} (A)	15.62	15.70	15.78	15.86	15.94
Module efficiency	η (%)	21.57	21.80	22.02	22.25	22.47
Power tolerance	(W)	0~+5				
Maximum system voltage	(V)	1500				
Maximum series fuse rating	(A)	30				

*STC: Standard Test Conditions (irradiance 1000 W/m², cell temperature 25°C and air mass of AM1.5), measurement tolerance P_{max} : ±3%

Electrical specifications (NMOT*):

Nominal max. power	P_{max} (Wp)	367	371	375	379	383
Maximum operating voltage	V_{MPP} (V)	30.40	30.60	30.80	31.00	31.20
Maximum operating current	I_{MPP} (A)	12.08	12.13	12.17	12.22	12.26
Open-circuit voltage	V_{oc} (V)	36.10	36.30	36.50	36.70	36.90
Short-circuit current	I_{sc} (A)	12.88	12.94	13.00	13.06	13.12

*NMOT: Normal Module Operating Temperature (irradiance 800 W/m², ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

Bifacial electrical specifications

Max. power front-side $P_{max front}$ (Wp)	480	485	490	495	500
Backside Power Gain	5% 10%	5% 10%	5% 10%	5% 10%	5% 10%
Total equivalent power $P_{max equ}$ (Wp)	504 528	509 534	515 539	520 545	525 550
Module efficiency η (%)	22.65 23.73	22.89 23.98	23.12 24.22	23.36 24.47	23.59 24.72

*Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on the mounting (structure, height, tilt angle, etc.) and albedo of the ground.

Mechanical and design specification

Cell type	n-Type TOPCon technology, half-cut cells
No. of cells	108
Bifaciality	80 ± 5%
Front cover	2.0 mm glass, high transmission, AR coated, tempered
Encapsulation	POE
Back cover	2.0 mm white glazed glass, tempered
Junction box	IP68 rated, 3 bypass diodes
Frame	30 mm anodized aluminium alloy
Cable (Including Connector)	1 x 4 mm², 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	1964 mm x 1133 mm x 30 mm
Weight	27.5 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m²
Snow load	5400 Pa or 550 kg/m²
Fire rating	Class A (according to UL 790)

Temperature ratings

Operating temperature	-40 to +85°C
Temp. coefficient of P_{max}	-0.30 %/°C
Temp. coefficient of V_{oc}	-0.24 %/°C
Temp. coefficient of I_{sc}	0.040 %/°C
Nom. operating cell temp. NOCT	43 ± 2°C

Packaging information

Packaging configuration	36 pcs / pallet
Loading capacity	864 pcs / 40 HQ
Size / Pallet	1990 mm x 1140 mm x 2500 mm (Upright)
Weight	1028 kg / pallet



+49 8231 978268 0
sales@ae-solar.com
www.ae-solar.com

AESOLAR
Messerschmitt 54
86343 Königsbrunn, Germany

Ver. 24.12.1

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.